LOOM SYSTEM FR

DESIGN MASSIMO CASTAGNA

STRUCTURE

Solidwood, thickness 4 cm.

HINGED DOOR

Frame in Brass and steel. Finish in Burnished Brass, Burnished black steel by hand using traditional techniques, stopsol glass 0,5 cm.

BACKREST

Heat treated woods as our samples and Swamp woods as per our samples.Burnished Platino, Burnished Titanio, Burnished Brass or H-Silver by hand using traditional techniques.

STORAGE UNITS WITH FLAP DOORS OR DRAWER


Solidwood, thickness 2 cm. Heat treated woods as our samples or swamp woods as per our samples finish based on natural wax and water. Optional finish: Burnished Black Brass, Burnished Brass, Burnished black steel, steel finish Burnished Platino, Burnished Titanio by hand using traditional techniques.

SHELVES

Bronzed tempered glass 1 cm thick. Metal shelves version with one shelf thickness 9 cm and one thickness 5 cm covered with metal.

Cm 86x55x234h

TECHNICAL DRAWINGS



CARE AND MAINTENANCE OF METALS

Avoid leaving household liquids (oil, red wine, vinegar, etc.) on the surface. In particular, products that contain citric acid (present for example in fruit, citrus fruit and tomatoes) act on contact with the treated surface, removing its original sheen. Always clean stains while they are still fresh. For routine maintenance use a microfiber cloth and water. Do not use products containing acids, limescale removing substances or alcohol.

CARE AND MAINTENANCE OF WOOD

The woods used for our products are of the highest quality and manufactured with the greatest craftsmanship. As wood is a natural material, when placed in a very dry environment it loses humidity and consequently shrinks. In contrast, in a very humid environment wood acquires humidity, increasing in size. These subtle reactions are not flaws but natural movements of a 'living' product, which expands and contracts as the seasons change. Furthermore, the final moisture content of wood also varies according to use, for which particular care is required. For routine maintenance of wood, use a soft, damp, fluffy cloth, or a microfiber cloth. Stubborn stains cleaning wood and does not scratch. To thoroughly clean even the finest grain, follow the direction of the grain using a neutral pH detergent. Next, rinse with a well wrung out cloth and thoroughly dry all surfaces. It is advisable to use neutral pH products and to always test any product on a small hidden part of the object before using it on the outside. To apply the rejuvenating oil provided, carefully follow the instructions printed on the packaging. Bear in mind, however, that the treatment does not make the surface immune to the effects of acidic substances (such as lemon juice). Specific cleaner and care kit for wooden surfaces, including specific products and accessories is available upon request.